



BoFloor
durable quality



BoProtect.

Moveable protective layer

www.bofloor.nl

Protect your sport hall for extra sport use



BoFloor BoProtect is the ideal moveable solution for protecting sport floors during non-sporting activities. It can be unrolled over floors and then rolled up again before resuming sports activities.



Efficient protection of the sport flooring



Easy to install and to remove for multiple uses



Sustainable protective solution



Specific range of equipment available

BoProtect installed on hardwood subfloor.



Made of 100% post-manufacturing waste



100% recyclable

MADE IN FRANCE



Antibacterial environments



TVOC emissions below detection level
(TVOC <100µg/m³ after 28 days)

BoProtect Moveable protective layer



- ① Special protective grain
Black: masking sober colour



Thin layer with special protective grain prevents marks and stains, easy maintenance



Customizable length every 0,5 lm from 12 lm to 45 lm
Width: 1,5 m



Outstanding fire resistance
Bfl-S1



Looselay and edge-to-edge installation can be secured with single-sided tape adhesive

Wide range of accessories to ease the installation

MOBILE OR STATIC STORAGE RACKS



SINGLE-SIDED TAPE AND UNROLLER



SERVING TROLLEYS



BoProtect

Moveable protective layer



DESCRIPTION	STANDARD	REQUIREMENT	UNITS	TARAFLEX® BATECO
PRODUCT DESCRIPTION				
Surface treatment	-	-	-	-
Surface complex	-	-	-	-
Foam	-	-	-	-
Thickness	EN ISO 24346 (EN 428)	-	mm	1,5
Weight	EN ISO 23997 (EN 430)	-	kg/m²	2,5
Length	EN ISO 24341 (EN 426)	-	ml	45 Max
Width	EN ISO 24341 (EN 426)	-	ml	1,5
TECHNICAL CHARACTERISTICS				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 300
Impact resistance	EN 1517	≥ 8	N/m	-
Indentation resistance	EN 1516	≤ 0,5	mm	≤ 0,5
Dimensional stability	EN ISO 23999	-	%	1
CLASSIFICATION				
Fire	EN 13501-1	-	-	Bfl-s1
Anti-bacterial activity (E. coli - S. aureus - MRSA ⁽¹⁾)	ISO 22196	-	-	> 99 % inhibits growth
CE MARKING				
CE	EN 14041	-	-	Fire
INSTALLATION METHODS				
	GERFLOR'S RECOMMENDATION		UNITS	RESULTS
LOOSE LAY ON THE EXISTING FLOORING	-	-	-	-

(1) The implementation of an effective cleaning method is the best defence against infection

www.bofloor.nl



a Havikweg 17
6374 AZ Landgraaf (NL)

Industrialarea Abdissenbosch
Parkstad 3381

t 0031-455322277
e info@bofloor.biz